

IN THE CLAIMS:

Please amend claims 1 and 14; and cancel claims 6 and 17, as follows:

1. (Currently Amended) An optical communications apparatus for power balancing a wavelength division multiplexed (WDM) signal output from an add module adding at least one channel to a signal input thereto, comprising:

a gain element optically coupled to the add module and to an add channel port receiving the added at least one channel ~~to be added~~;

Q1 said gain element imparting optical gain to the added at least one channel ~~received from the add channel port~~;

a controller operatively coupled to said gain element, said controller receiving an input power measurement of the signal input to the add module; and

an optical amplifier supplying said signal input to said add module, said controller determining an add path amplification value based on the input power measurement, a through loss associated with a signal passing through the add module, and an add loss associated with a signal ~~travelling~~ traveling an add path of the add module, ~~and,~~ said controller controlling said gain element according to the add path amplification value, such that a portion of a gain profile of said optical amplifier corresponding to a spectrum associated with said added at least

one channel substantially matches a portion of a gain profile of said gain element corresponding to said spectrum.

2. (Currently Amended) The optical communications apparatus for power balancing a wavelength division multiplexed (WDM) signal according to claim 1, wherein said controller receiving a number of channels to be added by the add module;

Q1
copy said controller determining the add path amplification value based on the number of channels to be added, the input power measurement, the through loss associated with a signal passing through the add module, and the add loss associated with a signal ~~travelling~~ traveling an add path of the add module; and

said controller controlling said gain element according to the add path amplification value.

3. (Currently Amended) The optical communications apparatus for power balancing a wavelength division multiplexed (WDM) signal according to claim 2,

said controller determining the add path amplification value based on the following equation:

$$P_{\text{addtotal}} = P_{\text{in}} + (\text{Add Loss} - \text{Through Loss}) + 10\text{Log}N_{\text{add}}$$

where

P_{addtotal} = add path amplified power level in dBm,

P_{in} = per channel power level of signal input to the add module in dBm,

Through Loss = loss associated with a signal passing through the add module in dBm,

Add Loss = loss associated with a signal ~~travelling~~ traveling an add path of the add module in dBm, and

N_{add} = number of added channels.

4. (Currently Amended) The optical communications apparatus for power balancing a wavelength division multiplexed (WDM) signal according to claim 1, further comprising:

al' conf
a coupler optically coupled to an input of the add module, an optical-to-electrical converter optically coupled to said coupler, said optical to-electrical coupler receiving a portion of light from the ~~input signal~~ added at least one channel input to the add module;

said controller determining the input power measurement from an output of said optical-to-electrical converter.

5. (Original) The optical communications apparatus for power balancing a wavelength division multiplexed (WDM) signal according to claim 1,

said controller receiving an added channel power measurement associated with ~~of~~ the added at least one ~~added~~ channel ~~being added by the add module;~~

said controller feedback controlling said gain element based on the added channel power measurement and the add path amplification value.

6. (Cancelled)

7. (Cancelled)

8. (Currently Amended) The optical communications apparatus for power balancing a wavelength division multiplexed (WDM) signal according to claim 1, further comprising:

an output amplifier optically coupled to the add module;

said output amplifier amplifying ~~the~~ an output of the add module.

a 9. (Currently Amended) The optical communications apparatus for power balancing a wavelength division multiplexed (WDM) signal according to claim 8,

said output amplifier performing gain flattening amplification for the ~~signal~~ output from the add module.

10. (Original) The optical communications apparatus for power balancing a wavelength division multiplexed (WDM) signal according to claim 1,

wherein said gain element includes an add amplifier,

said controller controlling said add amplifier according to the add path amplification value.

11. (Original) The optical communications apparatus for power balancing a wavelength division multiplexed (WDM) signal according to claim 1,

wherein said gain element includes an add amplifier and a variable optical attenuator,

said controller controlling said variable optical attenuator according to the add path amplification value.

12. (Original) The optical communications apparatus for power balancing a wavelength division multiplexed (WDM) signal according to claim 1,

wherein said gain element includes an add amplifier and a variable optical attenuator,

said controller controlling said variable optical attenuator and said add amplifier according to the add path amplification value.

13. (Original) The optical communications apparatus for power balancing a wavelength division multiplexed (WDM) signal according to claim 1,

wherein the add module is an add/drop module not dropping any channels.

14. (Currently Amended) A method of power balancing a wavelength division multiplexed (WDM) signal output from an add module adding at least one channel to a signal input thereto, comprising:

receiving an input power measurement of the signal input to the add module;

determining an add path amplification value based on the input power measurement, a through loss associated with a the signal passing through input to the add module and passing through

an optical amplifier, and an add loss associated with ~~a signal travelling~~ said added at least one channel traveling an add path of the add module; and

controlling an add path amplification of the add path according to the add path amplification value, such that a spectral portion of a gain profile of said optical amplifier corresponding to a spectrum associated with said added at least one channel substantially matches a portion of a gain profile of said gain element corresponding to said spectrum.

15. (Currently Amended) The method according to claim 14, further comprising the steps of:

receiving a number of channels to be added by the add module; and

determining the add path amplification value based on the number of channels to be added, the input power measurement, the through loss associated with a signal passing through the add module, and the add loss associated with ~~a signal travelling traveling~~ an add path of the add module said at least one added channel.

16. (Currently Amended) The method according to claim 15, further comprising:

~~determining~~ determining the add path amplification based on the following equation:

$$P_{\text{addtotal}} = P_{\text{in}} + (\text{Add Loss} - \text{Through Loss}) + 10\text{Log}N_{\text{add}}$$

where

$P_{addtotal}$ = add path amplified power level in dBm,

P_{in} = per channel power level of the signal input to the add module in dBm,

Through Loss = loss associated with a signal passing through the add module in dBm,

Add Loss = loss associated with a signal travelling an add path of the add module in dBm, and

N_{add} = number of added channels.

17. (Cancelled)

18. (Cancelled)

19. (Original) The method according to claim 14,

wherein the add path includes an add amplifier;

said controlling step controlling a gain of the add amplifier.

20. (Original) The method according to claim 14,

wherein the add path includes an add amplifier and a variable optical attenuator optically coupled thereto;

said controlling step controlling a gain of the add amplifier and/or an attenuation of the variable optical attenuator.

21. (Original) The method according to claim 14, amplifying the output of the add module.

22. (Original) The method according to claim 21,

said amplifying the output step including gain-flattening amplification.

*Al
cond.* 23. (Original) The method according to claim 14, wherein the add module is an add/drop module that is not currently dropping a channel.
